

## وحدة عدم انقطاع التيار الكهربائي SU 10K 3/1X



-1

:

True On Line Double Conversion – 10KVA/8KW

-2

:

(EMI/RFI FILTER – Surge

-

.IEEE 587 / ANSI C62.41

Suppression)

270 V → 485 V

:

-

.50 / 60

-

47 HZ → 53 HZ :

-

0.95

-

.

|    |                |                   |                     |    |
|----|----------------|-------------------|---------------------|----|
|    |                |                   | :                   | -3 |
|    |                | .(FILTER)         |                     | -  |
|    |                | 220/230/240V ± 2% | :                   | -  |
|    |                | 50/60 ± 0.2 HZ    | :(free running)     | -  |
| %3 | PURE SINE WAVE |                   |                     | -  |
|    |                | .                 |                     |    |
|    |                | %102              | :                   | -  |
|    |                | 60                | %125                |    |
|    |                | 30                | %150                |    |
|    |                | 2                 | %150                |    |
|    |                |                   | :                   | -4 |
|    |                | UPS               |                     | -  |
|    |                | .                 |                     |    |
|    |                |                   |                     | -  |
|    |                | % 90              | 4 – 2               | -  |
|    |                |                   |                     |    |
|    |                |                   | :                   | -5 |
|    |                | LCD               |                     | -  |
|    |                | .                 |                     |    |
| /  | (Inverter)     | (ByPass)          | 6                   | -  |
|    |                |                   | (Rectifier/Charger) |    |
|    |                | .                 |                     | -  |

**-6**

11

### Automatic By- Pass

—

UPS

**-7**

- 
- 

 $15^{\circ} \rightarrow 25^{\circ}\text{C}$ 

—

40° C      0° C

—

0% → 95%

—

3300 :

—

**-8**

6 3

## Sealed Lead Acid

—

( )

—

■

—

.. . 10

6 . . 5

18

—

18 . . 5

37

BP240V1ORT3U

—

.. 10



—

-9

—

■

—

■

■

|             |       |                    |      |
|-------------|-------|--------------------|------|
| RS400       | 3     | :                  | -    |
| Power Alert | RS232 | Contact Closure    |      |
|             | .(    | )                  |      |
|             |       | %90 :              | -    |
|             |       | 3:1 : Crest Factor | -    |
|             | (     | ) 1                | 55 : |
|             | .SNMP |                    | -    |
|             |       |                    | -    |
|             |       |                    | -    |
|             | EPO   |                    | -    |

·  
·

Tel: +218 21 4448630  
Fax: +218 21 4448612  
Email [Info@almohiet.net](mailto:Info@almohiet.net)