

وحدة عدم انقطاع التيار الكهربائي
SU 20K 3/3X



- 1 : True On Line Double Conversion – 20KVA/16KW
- 2 : (EMI/RFI FILTER – Surge Suppression)
- .IEEE 587 / ANSI C62.41
- 270 V → 485 V
- .50 / 60
- 47 HZ → 53 HZ :
- 0.95

			:	-3
		(FILTER)	-	
		380/400/415V ± 2%	:	-
		50/60 ± 0.1 HZ :(free running)	-	
%3	PURE SINE WAVE		-	
			.	
		%102	:	-
		60 %125		
		30 %150		
		2 %150		
			:	-4
		UPS	-	
			.	
		% 90	4 - 2	-
			:	-5
		LCD	-	
/	(Inverter)	(ByPass)	.	
			6	-
			(Rectifier/Charger)	-

: -6

" Automatic By- Pass

-

UPS

: -7

:

15° → 25°C

-

40° C 0° C

-

0% → 95%

-

3300 :

-

: -8

6 3

Sealed Lead Acid

-

()

-

-

.. . 20

17 . . 10

49

-

-

: -9

-

-

RS400	3	:	-
Power Alert	RS232	Contact Closure	-
	.()	-
		%90 :	-
		3:1 : Crest Factor	-
	1	60 :	-
.SNMP			-
			-
			-
	EPO		-

:

Tel: +218 21 4448630
Fax: +218 21 4448612
Email Info@almohiet.net