

وحدة عدم انقطاع التيار الكهربائي  
SU 30K 3/3X



	:	-1
True On Line Double Conversion – 30KVA/24KW		
	:	-2
(EMI/RFI FILTER – Surge		-
.IEEE 587 / ANSI C62.41	Suppression)	
270 V → 485 V	:	-
.50 / 60		-
47 HZ → 53 HZ :		-
0.95		-

: **-3**

.(FILTER) -

380/400/415V ± 2% :

50/60 ± 0.1 HZ :(free running) -

%3 PURE SINE WAVE -

%102 :

60 %125

30 %150

2 %150

: **-4**

UPS -

% 90 4 - 2 -

: **-5**

LCD -

/ (Inverter) (ByPass) 6 -

(Rectifier/Charger)

: -6

" Automatic By- Pass

-

UPS

: -7

:

15°→ 25°C

-

40° C 0° C

-

0% → 95%

-

3300 :

-

: -8

6 3

Sealed Lead Acid

-

( )

-

-

... 30

6 ... 15

18

-

-

: -9

-

-

RS400	3	:	-
Power Alert	RS232	Contact Closure	.( )
		%90 :	-
		3:1 : Crest Factor	-
	1	60 :	-
.SNMP			-
			-
			-
	EPO		-

:

Tel: +218 21 4448630  
 Fax: +218 21 4448612  
 Email [Info@almohiet.net](mailto:Info@almohiet.net)