

وحدة عدم انقطاع التيار الكهربائي SU 6000 RT3UHV



-1

:

True On Line Double Conversion – 6KVA/4200W

-2

:

(EMI/RFI FILTER – Surge

-

.IEEE 587 / ANSI C62.41

Suppression)

156 V → 276 V :

-

.50 / 60

-

47 HZ → 53 HZ :

-

0.99

-

-3

□

.(FILTER)

—

220 V $\pm$ 2% :

—

50/60 $\pm$ 0.05 HZ :(free running)

•

PURE SINE WAVE

—

-4

□
□

UPS

—

■

—

% 90

4 - 2

—

■

-5

□

□

LCD

—

■

6

—

/ (Inverter) (ByPass)

(Rectifier/Charger)

■

—

■

-6

□

□

11

Automatic By- Pass

—

UPS

■

40 ()

■

: -7

:

15°→25°C -

40° C 0° C -

. 0% → 95% -

: -8

Sealed Lead Acid () -

() 6 3 -

.

37 . 5000 20 . 6000 15 -

. 3000

79 . 6000 37 BP240V10RT3U -

. 3000

.

: -9

-

.

-

.

.

:

.()

Power Alert

.SNMP

EPO

() 19

.() U6

:

Tel: +218 21 4448630
Fax: +218 21 4448612
Email Info@almohiet.net