

وحدة عدم انقطاع التيار الكهربائي SUINT 3000 RTXL3U



-1

:

True On Line Double Conversion – 3KVA/2400W

-2

:

(EMI/RFI FILTER – Surge

-

.IEEE 587 / ANSI C62.41

Suppression)

130)

160 V → 275 V :

-

.(%70

.50 / 60

-

47 HZ → 53 HZ :

-

0.99

-

-3 :

- (FILTER)
- $220\text{ V} \pm 2\%$:
- $50/60 \pm 0.05\text{ HZ}$:(free running)
- PURE SINE WAVE

-4 :

- UPS

-
-
- $4 - 2$
- $\% 90$

-5 :

-
-
- (Inverter) / (ByPass)
- (Rectifier/Charger)
-

-6 :

- Automatic By- Pass
- UPS
- () 25 ()
- 10
-

: -7

:

15°→25°C -

40° C 0° C -

. 0% → 95% -

: -8

Sealed Lead Acid () -

() 6 3 -

. -

42 . 1500 17 . 3000 6 -

.() . 750

39 . 3000 17 BP72V12-2U -

. 1500

. -

: -9

-

.

-

.

.

	:	-
.(	)	
.		Power Alert
.SNMP		-
.		-
.		-
EPO		-
(	)	19
		. U3
. IEC320-C19	IEC320-C13	4 :
.		-

:

Tel: +218 21 4448630
Fax: +218 21 4448612
Email Info@almohiet.net